1

"LOOPED OPTICAL NETWORK WITH ASE LIGHT RECIRCULATION AND LINK AND NETWORK SURVIVABILITY CONTROL SYSTEM"

The present invention relates to a looped optical-
5 transmission network where at least one optical amplifier is needed to compensate for losses in the fibers and in the passive components and in particular in a transmission system operating with Wavelength Division Multiplexing (WDM) techniques.
10

In co-pending patent application WO 2004/064280 looped WDM networks are considered based on Erbium-Doped Fiber Amplifier" (EDFA) with recirculation of the Amplified Spontaneous Emissions (ASEs) in which each EDFA does not
15 include any gain-control mechanism and gain control is achieved automatically by ASE light recirculation in the loop.

In such networks, the light produced by the "lasing"
20 effect is generated at wavelengths which depend on the balance of the network sections and the EDFA structure.
In general, with a given EDFA structure the wavelength which gives peak gain in the EDFA cascade in the looped configuration depends on the losses in the sections. In
25 particular, by reducing this loss, the wavelength which gives peak gain will move from approximately 1532 nm towards the higher wavelengths like around 1560 nm for example.

2

Loss of the EDFA section and structure must be finely controlled so that peak gain appears at a wavelength λ_{ASE} that is well separated from the λ_1–λ_N band of the WDM signal. For example, a suitable WDM looped network

5 configuration based on ASE light recirculation can be implemented with $\lambda_{ASE} = 1532$ nm and 16 WDM channels spaced at 100 GHz and located between 1544 nm and 1558 nm.

The WDM looped network configuration based on ASE

10 light recirculation can give acceptable performance at very low cost. Indeed, ASE light recirculation gives an automatic gain control mechanism which avoids complex and costly devices and algorithms usually required for other EDFA-based standard WDM looped networks. In standard

15 configurations, ASE light can however increase in the loop in an uncontrolled manner leading to the arise of serious performance degradation which is strongly dependent on network operating conditions.

20 Basically, two solutions were proposed in the prior art with the purpose of keeping an undesired ASE increase under control. The first solution is based on a break in ASE circulation at a specific node in the loop. In this manner the problem is solved with the disadvantage of

25 having to introduce additional passive components and/or with system flexibility loss. Centralized traffic is necessary or any traffic reconfiguration requires the visit of the node realizing the ASE break. The second solution tries to keep the gain always below the "lasing" effect

3

threshold so that ASE recirculation cannot increase in
power by propagating along the loop. Neither solution is
however sufficiently effective and they require complex and
costly devices and algorithms. A problem with this approach

5   is that the EDFA or similar amplifiers have gain dependent
on the power applied at input and in the network the power
input to the amplifiers depends in turn on the number of
channels active at that moment. For this reason, to keep
total gain below the lasing threshold under all possible

10 conditions including the addition or removal of channels
and nodes, a complex algorithm for overall control of the
loop with many monitoring points is necessary or it is
necessary to hold gain of the individual amplifiers low
enough to ensure that, even under conditions leading to

15 maximum amplifier gain, the total gain in the network is
less than 1. This solution brings a considerable reduction
in the total performance achievable since, when maximum
gain conditions are far, amplification of the individual
amplifiers is much lower than might be achieved.

20

    In WDM looped networks based on ASE recirculation, the
signal power per channel at the EDFA input must be low
enough (for example -20 dBm/ch) to keep predominant the
lasing effect light at λ_{ASE} on each EDFA output. This

25 characteristic ensures that the transient effects due to
the WDM channel ADD and DROP operations will be limited.
Two main limiting factors were identified in the EDFA-based
WDM looped networks with ASE recirculation. The first is
that the peak wavelength of the gain and the Optical Signal

4

To Noise Ratio (OSNR) of the signal depend strongly on the
network section balance and the EDFA structure (length of
active fiber and pump power). This requires in each section
the use of optical attenuators and complex installation

5   procedures. Furthermore, to make the network operative
under stable conditions, high section losses must be
introduced with resulting performance reduction towards the
signal-to-noise ratio (OSNR). It can also be noted that
while the EDFA gain exactly compensates for the losses of

10   the sections and of the components at the λ_{ASE} wavelength of
the gain peak, the gain at the wavelengths of the signals
will be lower than with λ_{ASE}. The highest difference in gain
$\Delta Gmax$ at the lasing light and signal wavelengths must be
controlled. $\Delta Gmax$ should be high enough to avoid network

15   instability caused by gain peak wavelength variations
induced by WDM add and drop operations and/or loss
variations in the sections caused by ageing of components
and connectors. At the same time, $\Delta Gmax$ should be low
enough to ensure acceptable performance of the signal-to-

20   noise ration for the WDM signals propagated along the
looped network. It is difficult to find an optimal $\Delta Gmax$
without degrading network OSNR performance and ensure good
network stability at the same time.

25   The second important limiting factor is that with
failures of the fiber and/or an EDFA, strong signal power
ranges are expectable because of loss of the gain lock
mechanism supplied by recirculation. This effect must be
kept under control since these power transients can damage

5

the components in the receiving side of the EDFAs and generate other problems caused by nonlinear effects of propagation. It should be noted also that where there is breakage of fibers and/or EDFA, the extreme signal power ranges become ever greater and faster along the EDFA cascade.

To obtain the greatest advantages from the use of WDM looped networks based on ASE recirculation in terms of simplicity and cost reduction, it is very important to find suitable solutions able to improve OSNR performance, ensure sturdiness of the network in terms of section loss variations and network survival in case of fiber or EDFA breakage.

In the co-pending patent application WO 2004/064280 incorporated herein by reference a gain control method in a ring optical transmission system was proposed comprising along the ring rare earth doped fiber amplifiers and comprising positioning a gain peak at a wavelength (λ_{ASE}) outside the band (λ_1-λ_n) of the channels transmitted along the ring and corresponding to an ASE emission peak of the amplifiers in the ring and employing the lasing peak produced thus as a gain stabilization signal.

To supply a gain check of a single EDFA optical

6

amplifier it was proposed in the prior art to use a local oscillator at the amplifier to produce an auxiliary compensation wave added to the useful signal. A similar system is described for example in US 6,043,931. This

5   allows stabilization of the gain of a single amplifier but this is not at all useful for solving the above-mentioned problems of a looped network. The system proposed in US 6,043,931 realizes a gain stabilization which remains local at the individual amplifier since it is realized

10   through a gain link of the fully optical amplifier. Each amplifier of the network should therefore be realized in accordance with that patent. This is excessively costly and in any case an amplifier stabilized in this manner does not satisfy the above-mentioned overall needs of a looped

15   network, especially with ASE recirculation.

     The general purpose of the present invention is to remedy the above-mentioned shortcomings by making available a method and a network with an effective, economical and

20   sturdy system for link and network survivability control.

     In view of this purpose it was sought to provide in accordance with the present invention a looped WMD optical network comprising an optical loop with optical amplifiers

25   between loop sections and with ASE recirculation in the

7

loop and characterized in that at a point of the loop a laser beam is injected and allowed to circulate in the loop with the laser beam being centered around a λ_{LINK} wavelength where it is desired that a lasing peak be generated.

5

Preferably the λ_{link} wavelength is centred outside a band $(\lambda_1 - \lambda_n)$ of the channels to be transmitted on the loop.

Again in accordance with the present invention it was also sought to provide a method for control of the link in a WDM looped optical network comprising an optical loop with optical amplifiers between loop sections and ASE
10   recirculation in the loop in accordance with which a laser beam centered around a λ_{LINK} wavelength where it is desired to generate a lasing peak is injected at a point in the loop and made to circulate in the network.

15   To clarify the explanation of the innovative principles of the present invention and its advantages compared with the prior art there is described below with the aid of the annexed drawings a possible embodiment thereof by way of non-limiting example applying said
20   principles. In the drawings:

8

FIG 1 shows diagrammatically a looped network realized in accordance with the principles of the present invention,

5   FIGS 2 and 3 show graphs of the amplifier output spectrum of a prior art network in two different load conditions,

FIG 4 shows a graph of the behavior at the transient

10   of a generic prior art network,

FIGS 5 and 6 show graphs similar to those of FIGS 2 and 3 but applying the principles of the present invention,

15

FIG 7 shows a graph similar to the one of FIG 4 but applying the principles of the present invention,

FIGS 8 through 11 are graphs showing the amplifier

20   output spectrum from a network in accordance with the present invention and with possible variant embodiments of the network,

FIG 12 shows a graph similar to those of

25   FIGS 8 through 11 but without applying the principles of the present invention,

FIG 13 shows a block diagram of a node of the network realized in accordance with a possible variant

9

applying the principles of the present invention, and

FIGS 14, 15 and 16 show graphs of transient effects in
a network in accordance with the present invention in
5   different failure cases.

With reference to the figures, FIG 1 shows
diagrammatically a looped optical transmission network
where at least one optical amplifier is necessary to
10   compensate for losses in the fibers and in the passive
components and in particular in a transmission system
operating with Wavelength Division Multiplexing (WDM)
techniques.

15   The looped network designated as a whole by reference
number 10 applying the principles of the present invention
comprises an optical fiber loop 11 divided in sections
between which are nodes 12 comprising known optical
amplifiers 13 (for example EDFAs) and known devices 14 for
20   adding and dropping channels to and from the network at
input/output units 15. Each EDFA does not include a gain
centre mechanism and gain control is achieved automatically
by ASE light recirculation in the loop.

25   In accordance with the present invention one of the
looped network amplification nodes (called here "master"
and designated as a whole by reference number 16) is
equipped with a laser 17, advantageously a Distributed Feed
Back (DFB) type centered around 1532 nm (λ_{LINK}), i.e. in the

10

spectral region where it is desired that a lasing peak be generated. Advantageously, the laser beam powers at the EDFA input are chosen between −5 dBm and +10 dBm.

5   Under normal operating conditions the beam produced by the laser 17 is injected into the loop (advantageously upstream of the EDFA amplifier of the node) and allowed to circulate therein. This realizes the link control. As clarified below, it was surprisingly found that this
10 supplies good sturdiness of the network in terms of section loss variations and greatly improves the OSNR of the WDM signal.

Since in accordance with the present invention the
15 behavior of the network is strongly dependent on the presence of the additional laser beam which effects link control, to make the network more reliable a redundant laser generation system can be advantageously provided in the master node 16. In particular, the system can also
20 provide an additional DFB laser 18 which is lit if the first DFB 17 fails.

In addition, known Variable Attenuators (VOA) 29 can be provided at the output of each EDFA to be able to
25 standardize the loss of each section (for example at 4 x 19 dB as will be indicated below with reference to FIGS 2 and 3). With these attenuators it is easier, even with "link control", to control the gain peaking and force it to the wavelength desired, for example 1532 nm. With losses of

11

low sections corresponding for example to only 25 km of
fiber and fixed add/drop for few channels, the gain peaking
would form probably around 1560 nm. When the "link control"
is used the lasing peak is a single wavelength

5   corresponding to the link control wavelength. The lasing
light provided by ASE light recirculation controls each
EDFA, and using the "link control" forces the lasing light
to be at a given wavelength.

10   To learn and show the advantages of a network having
the link control mechanism in accordance with the present
invention, various experiments were carried out on a test
network. For the sake of simplicity, only four sections of
25 km of fiber each were used but the same conclusions can

15   be extended to a much higher number of sections.

The dynamic behavior of a test signal was observed
after propagation along the entire looped network and under
various addition (ADD) and subtraction (DROP) operations of

20   WDM channels with and without the link control at 1532 nm
of the present invention.

Under test conditions, three high-power WDM channels
were activated and deactivated through an Acoustic Optical

25   Modulator (AOM) to simulate 15 or 16 WDM channels added to
or subtracted from the master node where the link control
is inserted in the network.

The structure of the EDFA amplifier was kept simple to

12

meet low cost requirements. Approximately 10m of fiber doped with erbium ions with absorption peak at 1532 nm of approximately 7 dB/m are pumped both ways at 980 nm (total pump power: 100 mW).

5

FIGS 2 and 3 show the output spectra after the last EDFA in the looped network when the control in accordance with the present invention is not used. The section balance (4x19 dB) is such that the gain peak is between 1532 nm and 1560 nm. FIG 2 shows full load (all channels) and FIG 3 shows a single active channel.

It is noted that the associated low loss of the section can be advantageous in terms of OSNR performance (27 dB on a band amplitude resolution of 0.1 nm) but is not at all optimal in terms of dynamic behavior upon ADD and DROP of channels and as gain uniformity.

On this point, in the network without control in accordance with the present invention, FIG 4 shows the test power range at the output of the last EDFA induced by extinction of the three channels simulating full network load. Note the high transient for a network with control and formation of amplified spontaneous emission peaks in the spectral zone of the WDM signals. Such a looped network is based on ASE recirculation and would require a high section loss (at least 21 dB) to ensure steady operating

13

conditions while avoiding the risk of gain peaks caused by
the WDM channels. Satisfying this condition necessarily
induces poor performance concerning the OSNR and does not
supply acceptable performance with more than six sections.
In this specification recirculation means propagation
around the loop more than once. It will be appreciated that
optical components such as the high pass optical filter 20
may at least partially block a portion of the light
circulating or recirculating in the loop. However, the
devices 14 for adding and dropping channels only act on
these channels and leaves the ASE light free to pass
therethrough for recirculation in the loop.

        FIGS 5 and 6 show the output spectrum after the last
EDFA in the looped network with link control at 1532 nm and
the same section balance (4x19 dB) as in FIGS 2 and 3. Note
5   the very narrow spectrum of the peak at 1532 nm. It is
clear in this case that good OSNR performance can be
achieved without the risk of formation of amplified
spontaneous emission peaks in the spectral zone of the WDM
signals because of the ADD/DROP of WDM channels. If
10   FIGS 3 and 6 are compared, the nearly total lack of peak at
the upper limit of the signal band is also noted. It can
also be noted that the presence of the 1532 nm link control
avoids formation of a double ASE peak at 1532 nm to supply
greater sturdiness of the network in terms of effects
15   dependent upon polarization.

14

FIG 7 shows the behavior at the transient caused by the ADD/DROP of WDM channels in the network in accordance with the present invention. The loop gain is equal to the

5   loss at the gain peak wavelength so that the lasing action controls the transients. If compared with the result of FIG 4, ranges of much lower power can be noted, even if induced by the same ADD/DROPs as in FIG 4.

10   To further improve performance of the network in accordance with the present invention and also reduce the penalizations introduced by the spectral hole, a high-pass optical filter 20 can be easily introduced in the loop. It was found that the simple addition of such a filter

15   supplies additional improvement in OSNR performance of the entire network.

High-pass optical filters can be used to avoid accumulation of ASEs around 1532 nm and to force the lasing

20   effect at suitable wavelengths by introducing a link control positioned near the WDM signal band above or below the signal wavelength.

The high-pass filter can also be designed to realize

25   equalization in the gain of the WDM signal. In this case each amplifier node of the network can be equipped with such a filter.

Various combinations of filter and link control were

15

found advantageous as follows:

- a high-pass optical filter in the looped network to eliminate the accumulation of ASEs below 1535 nm and the link control positioned at a suitable wavelength between the filter cut-off wavelength and the WDM signal band (i.e. advantageously at 1537 nm),

- a high-pass optical filter in the looped network to eliminate accumulation of ASEs below 1538 nm and link control positioned at a wavelength slightly higher than the WDM signal band (i.e. advantageously at 1564 nm),

- a high-pass/gain equalizer optical filter in each amplifier network node with one cut-off wavelength around 1535 nm and link control positioned at a suitable wavelength between the filter cut-off wavelength and the WDM signal wavelength (i.e. advantageously at 1537 nm), and

- a high-pass/gain equalizer optical filter in each network amplifier node with a cut-off wavelength around 1538 nm and link control positioned at a suitable wavelength above the WDM signal wavelength (i.e. advantageously at 1564 nm).

As an example, FIGS 8, 9 and 10 show OSNR performance for a network in accordance with the present invention

16

characterized by a 8x20 dB section balance and 24 WDM channels spaced at 100 GHz and located between 1542 nm and 1561 nm with and without optical filters.

5   In particular, FIG 8 shows the output spectrum in case of a WDM looped network based on ASE recirculation with a link control at 1532 nm and without high-pass filter. FIG 9 is achieved by introducing a single high-pass optical filter with a cut-off wavelength at 1537 nm and a link 10 control at 1538 nm. Lastly, FIG 10 refers to the network with a single high-pass optical filter with cut-off wavelength at 1539 nm and link control at 1565 nm.

FIGS 9 and 10 show clearly an improvement in the OSNR 15 higher by 8 dB for the channels of shorter wavelength proving the effectiveness of using high-pass optical filters in combination with link control techniques in accordance with the present invention to improve the performance of WDM looped networks.
20

To further show the effectiveness of the link control mechanism combined with a high-pass optical filter to achieve great strength upon the variations of loss in the sections, the results achieved in a network having 8x17 dB 25 section losses can be considered.

FIG 11 shows the output spectrum achieved in such a network with link control at 1565 nm and a single high-pass optical filter with cut-off wavelength at 1539 nm.

17

Comparing this spectrum with the one shown in FIG 12 and
achieved in a network not having link control in accordance
with the present invention, it can be seen clearly that the
link control at 1565 nm avoids formation of gain peaks
5   below the WDM channel band.

It is noted that the link control at higher signal
band wavelength is more effective in supplying strength at
the loss variations in the sections in comparison with a
10   link control at lower wavelengths.

Another advantageous effect of the principles of the
present invention concerns the network survivability in
case of breaks or breakage of EDFA amplifiers or network
15   fibers.

Indeed, the strong power ranges detected in networks
not having control in accordance with the present invention
can seriously degrade network performance and even damage
20   receiver components especially in a break in an EDFA within
the looped network.

This can be easily observed in FIGS 14 and 15 where
the transients caused on the EDFA outputs because
25   respectively of a fiber break and an EDFA break are shown.
Propagation and increase in the effect along the cascaded
amplifiers in the loop should be noted.

It is clear that such power ranges which become

18

greater and faster along the EDFA cascade are not acceptable because they can damage the optical components and even induce performance degradation as a result of nonlinear propagation effects. This effect is particularly
5   damaging in case of EDFA breakage since there is no ASE light at the input of the next EDFA along the loop.

     In order to take full advantage of the ASE recirculation based WDM looped network in terms of
10   simplicity and cost reduction, it is very important to find suitable solutions capable of improving OSNR performance and at the same time ensure network survivability in case of fiber or EDFA breakage.

15   Thanks to the innovative principles of a network in accordance with the present invention it is possible to realize with limited additional costs a node amplifier structure ensuring network survival.

20   To this end, the network nodes which are not "master nodes" are realized in accordance with the diagram of FIG 13. Basically, each amplifier node (indicated by reference number 112 in FIG 13) in the looped network, possibly excepting the "master" node, is equipped with a
25   DFB laser 24 (advantageously with a maximum required output power of 10 dBm and emission wavelength around λ_{LINK}) which can be activated in case of network failure caused by fiber or EDFA breakage.

19

The device 112 has a detector of any breakage upstream thereof. To realize this detector it was found advantageous to use a simple optical circuit comprising at the EDFA input a 99/1 splitter 21 which takes a fraction of the

5   optical power circulating in the loop and sends it to a band-pass filter 22 centered around λ_{LINK} and with a band at -3 dB of a few nm. The filtered signal is sent to a known threshold detector 23 (for example with input photodiode 25 and suitable comparison electronics 26 of the signal

10   obtained) to detect the presence of lasing light within the loop at the filter wavelength. The detector 23 activates the laser 24 if the lasing light power detected falls below the threshold (determined to be a symptom of breakage along the loop upstream). A 90/10 splitter 27 will convey the

15   laser beam together with the input signals to the amplifier 28.

It is noted that only the first amplifier node 112 following a fiber or EDFA break will activate the

20   corresponding DFB laser 24 while all the other nodes will remain unchanged.

After restoration of normal network operating conditions the DFB laser 24 will shut off automatically

25   under control of the detector 26.

Naturally the node 112 can also comprise a known unit of ADD/DROP channels (not shown) similarly to the nodes 12 of FIG 1.

20

FIG 16 shows the behavior of the test channel transient induced be a break in an EDFA in a network realized in accordance with the present invention with the amplification nodes 112. It should be noted that the DFB laser 24 at 1532 nm for network survival is activated at −10 dBm on the EDFA input following the break with a delay of 5 microseconds caused by the response time of the electronic circuit realizing the threshold detector 23. From FIG 16 it is clear that activation of the DFB laser 24 at the first node following the EDFA break effectively prevents broad signal power ranges observed without a control mechanism in accordance with the present invention. It is now clear that the predetermined purposes have been achieved by making available a link control mechanism supplying network sturdiness in terms of section loss variations and improving the OSNR of the WDM signal under normal operating conditions. In addition, the link control mechanism can also be combined with the use of high-pass optical filters to further improve network OSNR performance and can also be used to ensure network survival in case of breakage of fibers or EDFA.

Whilst the described looped optical network is configured to operate on the C-Band between 1530 − 1565 nm it will be appreciated that the invention could be adapted for use with other bands such as the L-Band between 1565−1625 nm.

21

Naturally the above description of an embodiment applying the innovative principles of the present invention is given by way of non-limiting example of said principles within the scope of the exclusive right claimed here. For example, the network can have any extension and complexity and comprise additional known members for the specific application.